



SPECIFICATION

Electrical Specification	MONO -30	MONO -40	MONO -50	MONO -60	MONO -80	MONO -100	MONO -150	MONO -165	MONO -200	MONO -250	MONO -300	MONO -350	MONO -360	MONO -370	
Nominal maximum power (Pmax)	30W	40W	50W	60W	80W	100W	150W	165W	200W	250W	300W	350W	360W	370W	
Optimum operating Voltage (Vmp)	18.54V	18.18V	20.00V	19.7V	18.0V	17.90V	18.40V	19.25V	24.70V	30.02V	32.90V	39.06V	39.48V	39.90V	
Optimum Operating Current (Imp)	1.62A	2.2A	2.50A	3.05A	4.44A	5.59A	8.16A	8.57A	8.10A	8.33A	9.12A	8.96A	9.12A	9.28A	
Open Circuit Voltage (Voc)	22.68V	22.50V	24.60V	23.99V	22.10V	21.95V	22.70V	23.60V	31.00V	37.10V	39.85V	46.88V	47.30V	48.35V	
Short Circuit Current (Isc)	1.76A	2.37A	2.75A	3.34A	4.88A	5.87A	8.58A	9.00A	8.48A	8.74A	9.62A	9.69A	9.88A	9.93A	
Operating Temperature	-40°C~+85°														
Maximum System Voltage	1000V (IEC)/600V (UL)														
Maximum Series Fuse Rating	15A														
RFID	Yes														
Power Tolerance	0~+5W														
Temperature Coefficient															
Pmax	-0.45%/°C														
Voc	-0.35%/°C														
Isc	-0.060%/°C														
NOCT (Nominal Operating Cell Temperature)	45°C														
Mechanical Data															
Cell Type	Monocrystalline														
Cell Arrangement	36 (4x9)	36 (4x9)	36 (4x9)	36 (4x9)	40 (4x10)	36 (3x12)	36 (4x9)	36 (4x9)	48 (6x8)	60 (6x10)	60 (6x10)	72 (6x12)			
Dimensions	680x350x25	680x547x30	680x547x30	680x540x30	860x670x35	1200x540x35	1487x666x35	1487x666x35	1335x982x40	1640x992x40	1640x992x40	1956x992x40MM			
Weights	3.77 (kg)	4.8 (kg)	5.5 (kg)	5.9 (kg)	5.76 (kg)	7.0 (kg)	11.5 (kg)	11.5 (kg)	15.0 (kg)	19.0 (kg)	19.0 (kg)	22Kg			
Front Cover	Tempered glass														
Frame material	Anodized aluminum alloy														
Standard Packaging (Modules/Carton)	10 pcs	5 pcs	4 pcs				2 pcs				26 pcs/pallet & 2 pcs/carton				

Note:

- The above specifications pertain to the standard SPV Modules.
- Electrical specifications mentioned above are under standard test conditions as follows [a] light spectrum of AM 1.5 [b] an irradiation of 1,000 Watts per square meter and [c] a cell temperature of 25 degrees Centigrade. Normal production tolerance of 0~+5W
- Due to continuous process innovations, the modules supplied may differ from those specified above.

FACTORY ADDRESS

A: No: 30 Yongshun Road, Zhulin Town, Jintan District, Changzhou, Jiangsu Province, China
 T: +86519-82983001
 FAX: +8651982983000
 W: www.restarsolar.com
 E: info@restarsolar.com



SPECIFICATION

Electrical Specification	POLY -3	POLY -5	POLY -10	POLY -20	POLY -30	POLY -40	POLY -50	POLY -60	POLY -80	POLY -100	POLY -150	POLY -165	POLY -200	POLY -250	POLY -300	POLY -325	POLY -330	POLY -340	POLY -345	
Nominal maximum power (Pmax)	3W	5W	10W	20W	30W	40W	50W	60W	80W	100W	150W	165W	200W	250W	300W	325W	330W	340W	345W	
Optimum operating Voltage (Vmp)	8.8V	8.8V	17.43V	17.25V	18.54V	18.10V	17.22V	19.7V	19.6V	17.90V	18.32V	18.82V	24.3V	29.9V	36.5V	37.5V	37.8V	38.3V	38.5V	
Optimum Operating Current (Imp)	0.34A	0.57A	0.58A	1.16A	1.62A	2.21A	2.91A	3.05A	4.08A	5.59A	8.18A	8.76A	8.23A	8.36A	8.22A	8.67A	8.74A	8.88A	8.96A	
Open Circuit Voltage (Voc)	10.8V	10.8V	21.18V	21.2V	22.68V	22.00V	21.1V	23.99V	23.7V	21.9V	22.3V	23.22V	30.7V	37.3V	45.3V	46.1V	46.4V	46.8V	46.9V	
Short Circuit Current (Isc)	0.37A	0.62A	0.63A	1.27A	1.76A	2.41A	3.21A	3.34A	4.42A	6.03A	8.8A	9.23A	8.58A	8.81A	8.66A	9.15A	9.23A	9.38A	9.47A	
Operating Temperature	-40°C~+85°																			
Maximum System Voltage	1000V (IEC)/600V (UL)																			
Maximum Series Fuse Rating	15A																			
RFID	Yes																			
Power Tolerance	0~+5W																			
Temperature Coefficient																				
Pmax	-0.45%/°C																			
Voc	-0.35%/°C																			
Isc	-0.060%/°C																			
NOCT (Nominal Operating Cell Temperature)	45°C																			
Mechanical Data																				
Cell Type	Polycrystalline																			
Cell Arrangement	20 (4x5)	18 (2x9)	36 (4x9)	36 (4x9)	36 (4x9)	36 (4x9)	36 (3x12)	36 (4x9)	40 (4x10)	36 (3x12)	36 (4x9)	36 (4x9)	48 (6x8)	60 (6x10)	72 (6x12)					
Dimensions	185x185x17	300x190x17	420x260x17	540x350x25	680x350x25	670x430x30	813x547x30	860x540x30	860x670x30	1200x540x35	1487x666x35	1487x666x35	1335x982x40	1640x992x40	1956*992*40					
Weights	0.34 (kg)	0.67 (kg)	1.2 (kg)	2.98 (kg)	3.77 (kg)	4.2 (kg)	5 (kg)	5.9 (kg)	6 (kg)	7 (kg)	11.5 (kg)	11.5 (kg)	15.5 (kg)	19 (kg)	22 (kg)					
Front Cover	Tempered glass																			
Frame material	Anodized aluminum alloy																			
Standard Packaging (Modules/Carton)	20 pcs	20 pcs	20 pcs	10 pcs	10 pcs	5 pcs	5 pcs	4 pcs	4 pcs	4 pcs	2 pcs	2 pcs	2 pcs	2 pcs	26 pcs/pallet & 2 pcs/carton					

Note:

- The above specifications pertain to the standard SPV Modules.
- Electrical specifications mentioned above are under standard test conditions as follows [a] light spectrum of AM 1.5 [b] an irradiation of 1,000 Watts per square meter and [c] a cell temperature of 25 degrees Centigrade. Normal production tolerance of 0~+5W
- Due to continuous process innovations, the modules supplied may differ from those specified above.

FACTORY ADDRESS

A: No: 30 Yongshun Road, Zhulin Town, Jintan District, Changzhou, Jiangsu Province, China
 T: +86519-82983001
 FAX: +8651982983000
 W: www.restarsolar.com
 E: info@restarsolar.com